

**PAINT SPRAY BOOTH COATING PRODUCT SPECIFICATIONS**

Product Name: 030-FD White Water-Based Peelable Booth Coating (Fast Dry Formula)
Product Code: 030-FD

Intended Use: This product was designed as a peelable spray booth coating intended to make clean up of paint overspray quick and easy.

Special Properties:

1. Fast Dry formula allows for less downtime.
2. White film for better booth illumination.
3. Forms a tough flexible film that is easily peeled.
4. Non-Flammable in liquid state.
5. Higher-solids formula allows for greater coverage.

Typical Properties:

Color: White
Viscosity: 70-72 Krebs Units
Solids by Weight: 52% +/- 2%
Solids by Volume: 45% +/- 2%
Wt/Gallon: 9.6 lbs./gallon +/- 2%
Coverage (average): 350 Square Feet per gallon @ 2.0 Dry Mil

Application Data:

Method: Apply by pressurized spray
Reduction: None is necessary. 030-FD is designed to be used full-body
Substrate: Spray on clean, smooth steel
Cure: Air Dry 30 Minutes

Recommended Dry Film Thickness: Apply 2-3 dry mils

Recommended Wet Film Thickness: Apply 6-8 wet mils

Clean Up: Water for all clean-up

Storage: This is a water-based material and must be protected from freezing. If this product arrives frozen, the product should be returned to ambient temperature for 48 hours and thoroughly agitated prior to application.

Shelf Life: **12 Months**

This product is not designed for applications that are subject to periods of elevated temperatures or exposure to sunlight.

This product is recommended for application to many different types of surfaces. These surfaces include steel, galvanized steel, aluminum, and diecast. Chemco recommends that all surfaces be cleaned prior to use. **THIS PRODUCT IS NOT RECOMMENDED FOR USE IN SPRAYBOOTH BAKE OVENS.** Chemco recommends testing prior to use on any other type of surface.

For any questions regarding this product, please call 800-323-0431, fax 800-336-7706, email @ nbinfo@chemcomfg.com