



PAINT SPRAY BOOTH COATING PRODUCT SPECIFICATIONS

Product Name: 030-L White Water-Based Peelable Booth Coating
Product Code: 030-L

Intended Use: This product was designed as a peelable spray booth coating intended to make clean up of paint overspray quick and easy.

Special Properties:

1. White film for better booth illumination.
2. Fast Dry time
3. Forms a tough flexible film that is easily peeled.
4. Non-Flammable in liquid state.

Typical Properties:

Color: White
Viscosity: 75-80 Krebs Units
Solids by Weight: 38% +/- 2%
Solids by Volume: 24% +/- 2%
Wt/Gallon: 8.9 lbs/gallon
Coverage (average): 250-275 Square Feet per gallon @ 2.0 Dry Mil

Application Data:

Method: Apply by pressurized spray
Reduction: None is necessary. 030-L is designed to be used full-body
Substrate: Spray on clean, smooth steel
Cure: Air Dry 60 Minutes

Recommended Dry Film Thickness: Apply 2-3 dry mils
Recommended Wet Film Thickness: Apply 6-8 wet mils
Clean Up: Water for all clean-up
Storage: This is a waterborne material and must be protected from freezing. See Chemco's 030-L FREEZE-THAW (030-L-FT) for an alternative for freezing temperatures
Shelf Life: 12 months.

This product is not designed for applications that are subject to periods of elevated temperatures or exposure to sunlight.

This product is recommended for application to many different types of surfaces. These surfaces include steel, galvanized steel, aluminum, and diecast. Chemco recommends that all surfaces be cleaned prior to use. **THIS PRODUCT IS NOT RECOMMENDED FOR USE IN SPRAYBOOTH BAKE OVENS.**

Chemco recommends testing prior to use on any other type of surface.

For any questions regarding this product, please call 800-323-0431, fax 800-336-7706, email @ nbinfo@chemcomfg.com